

# **BLANK PAGE**



IS: 10228 - 1982 (Reaffirmed 1998)

### Indian Standard

# SPECIFICATION FOR SCHOOL BAG

(First Reprint SEPTEMBER 2000)

UDC 688.35: 371.89

© Copyright 1982

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Gr 3 October 1982

#### AMENDMENT NO. 1 APRIL 2003 TO

#### IS 10228: 1982 SPECIFICATION FOR SCHOOL BAG

( Page 4, clause 4.1) — Substitute the following for the the existing clause.

'4.1 The various components of the school bag shall be made from the materials specified in Table 1 or from other types of materials, suitable for the intended purpose, subject to the agreement between the purchaser and the supplier.'

[ Page 5, Table 1, Sl No. (iv) and (v) ] — Substitute the following for the existing:

SI No.	Components	Material	Conforming to
(1)	(2)	(3)	(4)
iv)	Sewing thread for body and	Sewing cotton thread, Variety No. 28 (165 dtex $\times$ 6) (6 cord, 3 strands, each 2 fold)	IS 1720:1978‡
	stra <b>ps</b>	or Sewing polyester thread Variety No. 9 (145 dtex × 6) or	IS 9543:1980§
		Any other suitable thread, as agreed to between purchaser and the manufacturer. Thread may be grey or any colour matching to the body colour	
V)	Sewing thread for piping	Sewing cotton thread, Variety No. 32 (74 dtex × 6) (6 cord, 3 strands, each 2 fold) or	IS 1720:1978‡
		Sewing polyester thread Variety No. 5 (145 dtex × 3) or  Any other suitable thread, as agreed to between purchaser and the manufacturer. Thread may be black or of same colour as that of piping	IS 9543:1980§

(Page 5, Table 1, footnotes) — Insert the following at the end:

(PCD 13)

<sup>&#</sup>x27;§Specification for spun polyester sewing threads.'

## Indian Standard SPECIFICATION FOR SCHOOL BAG

#### Travel Requisites Sectional Committee, CPDC 18

#### Chairman

#### Representing

Dr D. K. Ghosh

Khadi and Village Industries Commission, Bombay

Members

SHRI B. MAJUMDAR ( Alternate to

Dr D. K. Ghosh )

PROF MONI BANERJEE

SHRI A. T. BASAK

SHRI DIPANKAR BASU

SHRI R. S. BHAT

SURI B. S. BHATNAGAR SHRI B. DUTT ( Alternate )

SHRI P. CHAUDHURY

SHRI A. S. ATHALYE ( Alternate )

SHRIC, A. FERENS

SHRI J. C. FERENS ( Alternate ) SHRI M. M. GARG

SHRIR. S. GHOSH

SHRI N. J. IRANI

SHRIB. N. SAHA ( Alternate )

SHRI JANE ALAM

SHRI NAVIN MALHOTRA SHRI U. N. MENON

DR R. PANDA SHRI G. S. LAKHOTIA ( Alternate )

Prof Moni Baneriee and Associates, Calcutta

Directorate General of Supplies and Disposals, New

Arts & Prints Pvt Ltd, Calcutta

Maharashtra Small Scale Industries Development

Corporation Ltd, Bombay Bengal Waterproof Ltd, Calcutta

V.I.P. Industries Ltd. Bombay

The Premier Leather Crafts, Bombay

Tannery and Footwear Corporation of India Ltd.

Kanpur Directorate General of Technical Development, New

Delhi Universal Luggage Manufacturing Co Pvt Ltd.

Bombay

Export Promotion Council for Finished Leather & Leather Manufacturers, Government of Uttar Pradesh, Kanpur

Railway Board (Ministry of Railways), New Delhi Indian Airlines, New Delhi

National Engineering Industries Ltd, Calcutta

(Continued on page 2)

#### C Copyright 1982

#### BUREAU OF INDIAN STANDARDS

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

#### IS: 10228 - 1982

Instrs )

( Continued from page 1 )

#### Members

#### SHRIT, K. PARTHASARATHY

LT-COL C. M. RAMAKRISHNA
MAJ R. M. SINGH ( Alternate )
SHRI D. H. SHAH
SHRI N. H. SHAH ( Alternate )
DR A. S. SETHI,
Director ( Const Prods & Med

#### Representing

Central Leather Research Institute (CSIR), Madras Ministry of Defence (DGI), New Delhi

Jeewanlal (1929) Ltd, Calcutta

Director General, ISI ( Ex-officio Member )

#### Secretary

Shri B. K. Mahata Deputy Director ( Consr Prods & Med Instrs ), ISI

# Indian Standard SPECIFICATION FOR SCHOOL BAG

#### 0. FOREWORD

- **0.1** This Indian Standard was adopted by the Indian Standards Institution on 29 June 1982, after the draft finalized by the Travel Requisites Sectional Committee had been approved by the Consumer Products and Medical Instruments Division Council.
- **0.2** The school bag described in this standard is in three sizes 'Small' 'Medium' and 'Large', with two different designs in each size, for example, one with side strap and the other with back straps. The bag is provided with a patch pocket in front, piping all round the edges and buckles with straps for closure.
- **0.3** The school bags shall be provided with back strap or side strap or both, as agreed to between the purchaser and the manufacturer. A handle may also be provided if required by the purchaser.
- **0.4** This standard contains clauses which call for agreement between the purchaser and the manufacturer, which permit the purchaser to use his option for selection, to suit his requirements. The relevant clauses are **3.1**, **4.1**, **5.5**, **6.1** and **9.1**.
- **0.5** For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960\*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

#### 1. SCOPE

1.1 This standard covers the requirements for bags, used by school students for carrying books, writing material, and drawing instruments.

<sup>\*</sup>Rules for rounding off numerical values ( revised ).

#### IS: 10228 - 1982

#### 2. NOMENCLATURE

2.1 The nomenclature of the bag shall be as shown in Fig. 1.

#### 3. SHAPE AND DIMENSIONS

- 3.1 The shape and dimensions of the school bag shall be as shown in Fig. 1. It may also be made to other shapes and dimensions as agreed to between the purchaser and the manufacturer:
- 3.1.1 The length of back strap for 'small', 'medium' and 'large' size shall preferably be 430 mm, 455 mm and 470 mm respectively.
- 3.1.2 The length of side strap shall be adjustable by means of a buckle as shown in Fig. 1. The length shall be adjustable between 250 mm to 950 mm.

#### 4. MATERIAL

4.1 The various components of the school bag shall be made from the materials specified in Table 1. The school bag may also be made from other types of materials, suitable for the intended purpose, subject to the agreement between the purchaser and the manufacturer.

#### 5. MANUFACTURE, WORKMANSHIP AND FINISH

- **5.1.** The school bag shall be made from three pieces of material, that is, from, back with top flap and gusset.
- 5.2 The front portion shall be provided with a patch pocket for small articles for use in school as shown in Fig. 1. The bag may also be provided with two patch pockets in the front portion. The shape of the pocket or pockets should be such as to provide sufficient space for keeping lunch-box, pencil box, instrument box, etc. This may be done with or without gusset.
- 5.3 The bag shall be provided with minimum 10 mm wide piping at the pocket, top edges and the sides as shown in Fig. 1. The piping shall be of the material specified in Table 1.
- 5.4 The school bag shall be assembled 'lock stitch' or 'chain stitch' regulated to give 6 to 8 stitches per 25 mm. All ends shall be securely fastened, off and loose threads properly trimmed.
- 5.5 Two buckles with straps shall be provided in the bag for closure as shown in Fig. 1. A handle may also be provided if required by the purchaser.
- 5.6 The bag shall be neatly finished with straight and parallel rows of stitching, where required.

	(Clause 4.1)					
Sr. No.	Components	MATERIAL	Conforming to			
(1)	(2)	(3)	(4)			
i) B	ody, straps, pockets, etc	Double-texture rubberized fabrics or	IS: 6110-1971*			
		Single texture rubberized waterproof fabrics	IS: 5915-1970†			
		Any other suitable material, as agreed to between the purchaser and the manufacturer				
ii) P	iping	Double-texture rubberized fabric or Any other suitable material, as agreed to between the purchaser and the manufacturer	IS: 6110-1971•			
iii) B	uckles	Aluminium prongless or of any other rustproof metal	_			
	ewing thread for body and straps	Sewing cotton thread, Variety No. 13 (6 Ply × 10 Tex) Grey or any colour matching to the body-colour	IS: 1720-1978‡			
v) Se	ewing thread for piping	Sewing cotton thread, Variety No. 13 (6Ply x 10 Tex) black or of same colour as that of piping	IS: 1720-19 <b>78</b> ‡			

TABLE 1 MATERIAL FOR COMPONENTS OF SCHOOL BAG

5.7 The ends of buckle loops, side, back and buckle straps shall be properly tacked with the rows of stitches as shown in Fig. 1.

#### 6. SAMPLING

**6.1** Unless otherwise agreed to between the purchaser and the supplier, the procedure given in IS: 2500 (Part I)-1973\* shall be followed for sampling. The inspection level and sampling plan as given in **6.2** and **6.3** shall be followed.

<sup>\*</sup>Specification for double-texture rubberized fabrics.

<sup>+</sup>Specification for single texture rubberized waterproof fabrics.

<sup>#</sup>Specification for cotton sewing threads ( second revision ).

<sup>\*</sup>Specification for sampling inspection tables: Part I Inspection by attributes and by count of defects (first revision).

#### IS: 10228 - 1982

- 6.2 The scale of sampling shall correspond to inspection level III given in Table 1 of IS: 2500 (Part I)-1973\* for all the requirements specified in this standard.
- **6.3** The sampling plan shall correspond to AQL plans of 40 percent given in Table 2 of IS: 2500 (Part I)-1973\*.


#### 7. TEST

- 7.1 Drop Tests The school bag shall be fully loaded with books or any other suitable material, weighing 6 kg in case of 'small', 8 kg in case of 'medium' and 10 kg in case of 'large' size school bags. After filling the specified weight, the bags shall be closed, buckles fastened and hung on pegs at the wall, with the help of either the side strap or the back straps. The distance between the floor and the peg shall be 1.5 metre in case of side strap and 1.0 metre in case of back strap. The bags shall then be suddenly dropped and this operation shall be repeated 10 times. During or after the test the stitches shall not open, the straps and buckles shall not give way or come off the stitched tacks.
- 7.2 Handle Snatch Test The school bag shall be securely fixed in an inverted position on a rigid support, leaving the strap free for applying the load. The strap shall be suitably harnessed to distribute the load applied over the entire middle portion. A load of 50 N (5 kgf) shall be applied suddenly to the strap for a period of 30 seconds. This operation shall be repeated 10 times.
- 7.2.1 The weight may be applied either by means of spring balance or weights, suitably placed on a stirrup. During or after the test, the strap shall not have snapped, loosened or come off the stitching.

#### 8. MARKING

- 8.1 Each school bag shall be legibly marked with the following:
  - a) Manufacturer's name or registered trade-mark,
  - b) Size, and
  - e) Year of manufacture in case of rubberized fabric.

<sup>\*</sup>Specification for sampling inspection tables: Part I Inspection by attributes and by count of defects (first revision).



All dimensions in millimetres.

Fig. 1 School Bag

- 8.2 The product may also be marked with Standard mark.
- **8.2.1** The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The details of conditions under which the licence for the use of Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

#### 9. PACKING

**9.1** Each school bag shall either be packed first in alkathene bag and then in any other suitably packing material to ensure safe transportation, or as agreed to between the purchaser and the supplier.

#### **BUREAU OF INDIAN STANDARDS**

#### Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 323 0131, 323 3375, 323 9402 Fax :+ 91 011 3234062, 3239399, 3239382

E - mail: bis@vsnl.com. Internet: http://wwwdel.vsnl.net.in/bis.org

Central Laboratory:					
Plot No. 20/9, Site IV, Sahibabad Industrial Area, Sahibabad 201010	77 00 32				
Regional Offices:					
Central: Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002					
*Eastern: 1/14 CIT Scheme VII, V.I.P. Road, Kankurgachi, CALCUTTA 700054					
Northeim: SCO 335-336, Sector 34-A, CHANDIGARH 160022					
Southern: C.I.T. Campus, IV Cross Road, CHENNAI 600113					
†Western : Manakalaya, E9, MIDC, Behind Marol Telephone Exchange, Andheri (East), MUMBAI 400093					
Branch Offices:					
Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 380001	550 13 48				
‡Peenya Industrial Area, 1st Stage, Bangalore-Tumkur Road, BANGALORE 560058					
Commercial-cum-Office Complex, Opp. Dushera Maidan, E-5 Arera Colony, Bittan Market, BHOPAL 462016	72 34 52				
62/63, Ganga Nagar, Unit VI, BHUBANESWAR 751001	40 36 27				
Kalai Kathir Building, 670 Avinashi Road, COIMBATORE 641018	21 01 41				
Plot No. 43, Sector 16 A, Mathura Road, FARIDABAD 121001	28 88 01				
Savitri Complex, 116 G.T. Road, GHAZIABAD 201001	71 19 98				
53/5 Ward No.29, R.G. Barua Road, 5th By-lane, GUWAHATI 781003	54 11 37				
5-8-56C, L.N. Gupta Marg, Nampally Station Road, HYDERABAD 500001	320 10 84				
E-52, Chitranjan Marg, C- Scheme, JAIPUR 302001	37 38 79				
117/418 B, Sarvodaya Nagar, KANPUR 208005	21 68 76				
Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kishore Road, LUCKNOW 226001	21 89 23				
NIT Building, Second Floor, Gokulpat Market, NAGPUR 440010	52 51 71				
Patliputra Industrial Estate, PATNA 800013	2 <b>6,2</b> 8 08				
Institution of Engineers (India) Building, 1332 Shivaji Nagar, PUNE 411005	32 36 35				
'Sahajanand House' 3rd Floor, Bhaktinagar Circle, 80 Feet Road, RAJKOT 360002	36 85 86				
T.C. No. 14/1421, University P. O. Palayam, THIRUVANANTHAPURAM 695034	32 21 04				
*Sales Office is at 5 Chowringhee Approach, P.O. Princep Street, CALCUTTA 700072	27 10 85				
†Sales Office is at Novelty Chambers, Grant Road, MUMBAI 400007					
‡Sales Office is at 'F' Block, Unity Building, Narashimaraja Square, BANGALORE 560002	222 39 71				